



TS12CC1R Carbon Monoxide Gas Detector



Product Description:

TS12CC1R are ideally suitable for applications where additional safety is required. The detector is positioned in such a way that gas leakage is detected as soon as possible. The output of the detector is PFC relay.

Product Features & Specifications:

- Latest electrochemical technology is used
- Dustproof & Water Splash proof – IP65 Enclosure
- Replaceable Filter
- Only Commercial Detector available with LEL Bargraph
- No Calibration required

Technical Specifications:

Gas Sampling	Natural diffusion	Detection Level	30ppm after 120 min, 50ppm - 60ppm to 90 min 100ppm - 10ppm to 40 min 300ppm < 3 minutes
Gas Sensor Type	Semi-Conductor	Output	PFC relay, Bar-graph LED
Power supply	12-30VDC		RS-485(Optional).
Power Consumption	2W Max.	Working Temperature	0°C to 50°C

Application:

- Home, Residential Use, Restaurant Kitchens,
- School Class Rooms
- Public Places like Mall, Movie Theatres, Car parking area.
- HVAC Air Quality Applications
- Optionally other detector model [TS12C(CO)R] can be provided PFC relay out-put and it can interfaced with alarm panels. This model is useful for commercial use like Car parking areas.

Realty Automation & Security Systems Pvt. Ltd.

5, New Sadashiv Peth, Next to Alka Talkies, Pune-411 030. Phone: +91 90110 33259/60.

E-mail: sales@vighnaharta.in

Web: www.vighnaharta.in