

FIRE SUPPRESSION SYSTEM

FEATURES

- 2 IDC can be cross zone assigned for single RAC & NAC.
- Fire / Fault Status in Unambiguous Colors LED indication
- Programmable Inputs for Pressure Switch
- Inhibit / Abort Switch & Instant Release Switch
- Programmable Mode (Auto / Manual) Selection & Zone Isolation Facility
- RAC Monitoring, BMS Connectivity
- Up to 1000 Events Memory Log Support
- Ultra Safe Triple Activation Logic to Avoid Accidental Release



GAS RELEASE PANELS

AVAILABLE MODELS

MODEL NOS.	ZONES	RELEASE
FSS-021G	2	1 Gas Release
FSS-042G	4	4 Gas Release
FSS-021D	2	1 Aerosol Release
FSS-042D	4	2 Aerosol Release
FSS-084D	8	4 Aerosol Release
FSS-0168D	16	8 Aerosol Release

CONVENTIONAL DEVICES



MODEL NOS.

SD9-1 / SD9-10

Battery Operated Smoke Detector

Smoke Detector with 1 Year Battery Life

MODEL NOS.

SD 12 / SD 12R / SH D12
2/4 Wire Smoke Detector

Conventional Smoke Detector 2 Wired

MODEL NOS.

HD 12 Heat Detector

Conventional Heat Detector 2 Wired

Standalone Smoke Detector with
10 Year Battery Life

Conventional 4 Wire Smoke Detector

Conventional Smoke + Heat Detector 2 Wired



Manual Call Point Plastic Box Mount



Response Indicator



Siren With Flasher